

TITLE :- STANDARD PRODUCT LIST V4 SLIM RADIAL FLOW (82MM)

V4 Slim R2 SERIES 1 Ø 220 volts, 50 Hz

| V4 MOTOR MAX OD 82 MM 1 PH 220 VOLTS, 50 HZ. | | | | | | | PUMP SS JACKET WITH NORYL DIFFUSER & IMPELLERS | | | | | | | | |
|--|----------------|---------|-------|------|-----|-----------|--|-----|-------|-----|-----|-----|-----|----|----|
| V4 SLIM R2 SERIES | | | | | | | DISCHARGE IN LPM | | | | | | | | |
| Sr. No. | Model | H.P | Stage | K.W | D.O | % Effi. | TOTAL HEAD IN METERS | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 |
| 1 | E10 R2 0.5 | 0.5 1Ø | 10 | 0.37 | 25 | 21 | | 40 | 37 | 35 | 30 | 25 | 20 | 15 | 10 |
| 2 | E15 R2 0.7 | 0.75 1Ø | 15 | 0.55 | 25 | 22 | | 60 | 56 | 52 | 45 | 37 | 30 | 22 | 15 |
| 3 | E20 R2 1.0 | 1 1Ø | 20 | 0.75 | 25 | 24 | | 80 | 75 | 70 | 60 | 50 | 40 | 30 | 20 |
| 4 | E25 R2 1.25 | 1.25 1Ø | 25 | 0.93 | 25 | 25 | | 100 | 94 | 87 | 75 | 62 | 50 | 37 | 25 |
| 5 | E30 R2 1.5 | 1.5 1Ø | 30 | 1.1 | 25 | 26 | | 120 | 112.5 | 105 | 90 | 75 | 60 | 45 | 30 |
| 6 | E40 R2 2.0 | 2.0 1Ø | 40 | 1.5 | 25 | 27 | | 160 | 150 | 140 | 120 | 100 | 80 | 60 | 40 |
| 7 | E50 R2 2.5 | 2.5 1Ø | 50 | 1.83 | 25 | 28 | | 200 | 187.5 | 175 | 150 | 125 | 100 | 75 | 50 |