

V4 OIL FILLED (THREE PHASE)

STANDARD PRODUCT LIST V4 OIL FILLED (THREE PHASE)													
V4 Motor Max OD 96 mm 3 Ph 415 Volts, 50 Hz						Pump with Noryl Diffuser & Impellers							
V4 OR1-T Series						DISCHARGE IN LPM							
Sr	Model	H.P	Stage	K.W.	D.O.	15	20	25	35	40	50	55	65
1	A08 OR1-T 1.0	1	8	0.75	1"	56	52	44	40	36	28	24	20
2	A10 OR1-T 1.0	1	10	0.75	1"	70	65	55	50	45	35	30	25
3	A12 OR1-T 1.0	1	12	0.75	1"	84	78	66	60	54	42	36	30
4	A18 OR1-T 1.5	1.5	18	1.1	1"	126	117	99	90	.81	63	54	45
5	A24 OR1-T 2.0	2	24	1.5	1.5"	168	156	132	120	108	84	72	60
6	A30 OR1-T 3.0	3	30	2.2	1.5"	210	195	165	150	135	105	90	75
7	A32 OR1-T 3.0	3	32	2.2	1.5"	224	208	176	160	144	112	96	80
8	A34 OR1-T 3.0	3	34	2.2	1.5"	238	221	187	170	153	119	102	85
V4 OR2-T Series						DISCHARGE IN LPM							
Sr	Model	H.P	Stage	K.W.	D.O.	10	15	20	30	35	45	50	60
1	A14 OR2-T 1.0	1	14	0.75	1"	98	91	77	70	63	49	42	35
2	A16 OR2-T 1.0	1	16	0.75	1"	112	104	88	80	72	56	48	40
3	A20 OR2-T 1.5	1.5	20	1.1	1"	140	130	110	100	90	70	60	50
4	A24 OR2-T 1.5	1.5	24	1.1	1.5"	168	156	132	120	108	84	72	60
V4 OR3-T Series						DISCHARGE IN LPM							
Sr	Model	H.P	Stage	K.W.	D.O.	40	45	50	60	65	70	80	85
1	A08 OR3-T 1.0	1	8	0.75	1.5"	56	52	44	40	36	28	24	20
2	A12 OR3-T 1.5	1.5	12	1.1	1.5"	84	78	66	60	54	42	36	30
3	A14 OR3-T 2.0	2	14	1.5	1.5"	98	91	77	70	63	49	42	35
4	A16 OR3-T 2.0	2	16	1.5	1.5"	112	104	88	80	72	56	48	40
5	A20 OR3-T 3.0	3	20	2.2	1.5"	140	130	110	100	90	70	60	50
6	A24 OR3-T 3.0	3	24	2.2	1.5"	168	156	132	120	108	84	72	60
V4 OR4-T Series						DISCHARGE IN LPM							
Sr	Model	H.P	Stage	K.W.	D.O.	30	40	50	60	70	80	85	90
1	A15 OR4-T 1.5	1.5	15	1.1	1.5"	82	75	67	60	52	45	37	30
2	A19 OR4-T 2.0	2	19	1.5	1.5"	105	95	85	76	66	57	47	38
3	A20 OR4-T 2.0	2	20	1.5	1.5"	110	100	90	80	70	60	50	40
4	A22 OR4-T 3.0	3	22	2.2	1.5"	121	110	99	88	77	66	55	44
5	A25 OR4-T 3.0	3	25	2.2	1.5"	138	125	113	100	87	75	62	50
6	A27 OR4-T 3.0	3	27	2.2	1.5"	149	135	122	108	94	81	67	54
V4 OR5-T Series						DISCHARGE IN LPM							
Sr	Model	H.P	Stage	K.W.	D.O.	50	60	80	90	110	120	130	140
1	A10 OR5-T 1.5	1.5	10	1.1	1.5"	55	50	45	40	35	30	25	20
2	A12 OR5-T 2.0	2	12	1.5	1.5"	66	60	54	48	42	36	30	24
3	A19 OR5-T 3.0	3	19	2.2	1.5"	105	95	85	76	66	57	47	38
V4 OR7-T Series						DISCHARGE IN LPM							
Sr	Model	H.P	Stage	K.W.	D.O.	60	80	100	120	130	140	150	170
1	A05 OR7-T 1.0	1	5	0.75	1.5"	30	27	25	22	20	17	15	12
2	A07 OR7-T 1.5	1.5	7	1.1	1.5"	42	38	35	31	28	24	21	17
3	A10 OR7-T 2.0	2	10	1.5	1.5"	60	55	50	45	40	35	30	25
4	A12 OR7-T 3.0	3	12	2.2	1.5"	72	66	60	54	48	42	36	30
5	A15 OR7-T 3.0	3	15	2.2	1.5"	90	82	75	67	60	52	45	37